ITS413 – Quiz 5

Name:

ID:

Mark: _____ (out of 10)

Question 1 [2 marks]

A Voice over IP application samples the input voice signal at a frequency of 8kHz, with each sample represented by 6 bits.

a) At what rate, in bits per second, is the voice data generated at? [0.5 mark]

Consider the overhead of VoIP. Assume the VoIP application generates packets that each contain 40 Bytes of voice data. Each packet has an additional 20 byte IP header, and 8 bytes of UDP header and 12 byte RTP header.

b) What network throughput is required to deliver the voice data to the destination at the same rate at which it is generated at the source? [1.5 marks]

Question 2 [6 marks]

Fill in the blank spaces (1 mark each)

- a) Video applications can tolerate some _____, whereas web browsing applications cannot.
- b) ______ are often used to reduce the effects of network jitter in streaming applications.
- d) In RTP, ______ can be used to convert from one data rate to another during a multimedia session.
- e) For an IPTV access network, ______ is better than ______ because it delivers optical fibre closer to the user's home.
- f) A common signaling protocol used in IP networks is ______.

Question 3 [2 marks]

Consider IP multicast versus using unicast to emulate a multicast network.

a) Explain an advantage of multicast.

b) Explain an advantage of using unicast to emulate a multicast network.